

RZT
SPECIFICATION SHEETS
2004-2012

2004	Specification Sheet	CC
2005	Specification Sheets	CC
2006	Specification Sheets	CC
2007	Specification Sheets	CC
2008	Specification Sheets	CC
2009	Specification Sheets	CC
2010	Specification Sheets	CC
2011	Specification Sheets	CC
2012	Specification Sheets	CC

Material contained in this document is intended for use by Independent Retail dealer personnel.

Any other use without expressed written consent of MTD PRODUCTS INC is prohibited.

RZT 17	17 H.P. Intek	Single	Hydro	2004
RZT 22	22 H.P. Intek	Twin	Hydro	2004

MODEL: RZT 17

YEAR: 2004

Factory Model Number: 17AA5A4G710, 17AA5A4G712

17 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Intek (Vertical)
Model/Type/Spec	31G777-0036
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	17 HP
Peak Torque	Not Available
Displacement	30.59 cu in. (501.2cc)
Bore	3.4375"
Stroke	3.0625"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.004" (0.1016 mm)
Valve Lash (Exhaust)	0.006" (0.1524 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.010"-0.014"

CAPACITIES:

Engine Crankcase	1.5 qts. (A)
Coolant	Not Applicable
Transmission	126 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-698083
Pre Filter	BS-697015
Oil Filter	BS-492932
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-492341
Points	Not Applicable
Carb Kit	BS-697241

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	BS-691188
Solenoid	725-1426
Muffler	751-0617A
Battery	925-1707D
Relays	725-04164
P.T.O. Clutch	917-04127

ENGINE:

Complete Engine	BS-31G777-0036
Short Block	BS-697762
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 22

YEAR: 2004

Factory Model Number: 17AA5A7P710, 17AA5A7P712

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	Not Available
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Intek (Vertical)
Model/Type/Spec	407577-0027
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	Not Available
Displacement	40.0 cu in. (656cc)
Bore	2.97"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	126 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-691005
Pre Filter	BS-273638S
Oil Filter	BS-492932
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-699814

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	BS-691188
Solenoid	725-1426
Muffler	751-0616A
Battery	925-1707D
Relays	725-04164
P.T.O. Clutch	917-04127

ENGINE:

Complete Engine	BS-407577-0027
Short Block	BS-692714
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	17 H.P. Intek	Single	Hydro	2005
RZT 50	22 H.P. Intek	Twin	Hydro	2005

MODEL: RZT 42**YEAR: 2005**

Factory Model Number: 17BA5A4G710, 17BA5A4G712

17 H.P. Hydro Drive
Electric P.T.O. / 42" Deck**GENERAL INFO:**

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Intek (Vertical)
Model/Type/Spec	31G777-0036
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	17 HP
Peak Torque	Not Available
Displacement	30.59 cu in. (501.2cc)
Bore	3.4375"
Stroke	3.0625"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.004" (0.1016 mm)
Valve Lash (Exhaust)	0.006" (0.1524 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.010"-0.014"

CAPACITIES:

Engine Crankcase	1.5 qts. (A)
Coolant	Not Applicable
Transmission	126 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-698083
Pre Filter	BS-697015
Oil Filter	BS-492932
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-492341
Points	Not Applicable
Carb Kit	BS-697241

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	BS-691188
Solenoid	725-1426
Muffler	751-0617A
Battery	925-1707D
Relays	725-04164
P.T.O. Clutch (B085 & Before)	917-04127
P.T.O. Clutch (See CC-491)	917-04183

ENGINE:

Complete Engine	BS-31G777-0036
Short Block	BS-697762
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2005

Factory Model Number: 17BA5A7P710, 17BA5A7P712

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Intek (Vertical)
Model/Type/Spec	407577-0317
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	Not Available
Displacement	40.0 cu in. (656cc)
Bore	2.97"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	126 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-691005
Pre Filter	BS-273638S
Oil Filter	BS-492932
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-699814

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	BS-691188
Solenoid	725-1426
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch (B085 & Before)	917-04127
P.T.O. Clutch (See CC-491)	917-04183

ENGINE:

Complete Engine	BS-407577-0027
Short Block	BS-692714
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	17 H.P. Courage	Single	Hydro	2006
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2006
RZT 50	22 H.P. Courage	Twin	Hydro	2006

MODEL: RZT 42

YEAR: 2006

Factory Model Number: 17AA5B4G710, 17AA5B4G709

17 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV530-0022
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	17 HP (12.7 kW)
Peak Torque	Not Available
Displacement	32.6 cu in. (535cc)
Bore	3.50"
Stroke	3.38"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.007" (0.178 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	1.6 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-20-883-06-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-20-584-03-S
Points	Not Applicable
Carb Kit	KH-12-757-03

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0617A
Battery	925-1707D
P.T.O. Clutch	917-04622

ENGINE:

Complete Engine	KH-SV530-0022
Short Block	KH-20-522-02
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
P.T.O. Clutch	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2006

Factory Model Number: 17AA5D7P710, 17AA5D7P709, 17AA5D7P756

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH661V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04622

ENGINE:

Complete Engine	KM-FH661V-AS05S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
P.T.O. Clutch	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2006

Factory Model Number: 17AA5B7P710, 17AA5B7P756

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV720-0012
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP (16.4 kW)
Peak Torque	Not Available
Displacement	44.00 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04622

ENGINE:

Complete Engine	KH-SV720-0012
Short Block	KH-32-522-03
Mini Block	Not Available

WARRANTY:

Limited Residential	2 Year
Engine	2 Year
P.T.O. Clutch	2 Year

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	17 H.P. Courage	Single	Hydro	2007
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2007
RZT 54	25 H.P. Kawasaki	Twin	Hydro	2007

MODEL: RZT 42

YEAR: 2007

Factory Model Number: 17AE2ACG710, 17AE2ACG709, 17AE2ACG756

17 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV530-0022
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	17 HP (12.7 kW)
Peak Torque	Not Available
Displacement	32.6 cu in. (535cc)
Bore	3.50"
Stroke	3.38"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.007" (0.178 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	1.6 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-20-883-06-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-20-584-03-S
Points	Not Applicable
Carb Kit	KH-12-757-03

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0617A
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV530-0022
Short Block	KH-20-522-02
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2007

Factory Model Number: 17AI2ACP710, 17AI2ACP709, 17AI2ACP756

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH661V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04622

ENGINE:

Complete Engine	KM-FH661V-AS05S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54

YEAR: 2007-2009

Factory Model Number: 17AI2ACK010, 17AI2ACK710, 17AI2ACK709,
17AI2ACK056

25 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH721V-AW04
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	25 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675 mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FH721V-ES25S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	20 H.P. Courage	Single	Hydro	2008
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2008
RZT 54	25 H.P. Kawasaki	Twin	Hydro	2008

MODEL: RZT 42

YEAR: 2008-2009

Factory Model Number: 17AE2ACG010

20 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV600-0028
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	Not Available
Displacement	36.4 cu in. (597cc)
Bore	3.70"
Stroke	3.38"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.007" (0.178 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	1.6 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-20-883-06-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-20-584-03-S
Points	Not Applicable
Carb Kit	KH-12-757-03

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-04439
Muffler	751-0617C
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV600-0028
Short Block	KH-20-522-01
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2008-2009

Factory Model Number: 17AI2ACP009, 17AI2ACP010, 17AI2ACP056, 17AI2ACP256,
17RI2ACP056, 17RI2ACP256, 17AI2ACP709

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH661V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FH661V-AS05S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54

YEAR: 2007-2009

Factory Model Number: 17AI2ACK010, 17AI2ACK710, 17AI2ACK709,
17AI2ACK056

25 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH721V-AW04
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	25 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675 mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FH721V-ES25S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	20 H.P. Courage	Single	Hydro	2009
RZT 42	20 H.P. Kawasaki	Single	Hydro	2009
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2009
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2009
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2009
RZT 50 VT	24 H.P. Intek	Twin	Hydro	2009
RZT 54	23 H.P. Kawasaki	Twin	Hydro	2009
RZT 54	23 H.P. Kawasaki	Twin	Hydro	2009
RZT 54	25 H.P. Kawasaki	Twin	Hydro	2009

MODEL: RZT 42

YEAR: 2008-2009

Factory Model Number: 17AE2ACG010

20 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV600-0028
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	Not Available
Displacement	36.4 cu in. (597cc)
Bore	3.70"
Stroke	3.38"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.007" (0.178 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	1.6 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-20-883-06-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-20-584-03-S
Points	Not Applicable
Carb Kit	KH-12-757-03

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-04439
Muffler	751-0617C
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV600-0028
Short Block	KH-20-522-01
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 42

YEAR: 2009-2010

Factory Model Number: 17AE2ACG010

20 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV600-0221
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	Not Available
Displacement	36.4 cu in. (597cc)
Bore	3.70"
Stroke	3.38"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.007" (0.178 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	1.6 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-20-883-06-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-20-584-03-S
Points	Not Applicable
Carb Kit	KH-12-757-03

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-04439
Muffler	751-0617C
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV600-0225
Short Block	KH-20-522-05
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2008-2009

Factory Model Number: 17AI2ACP009, 17AI2ACP010, 17AI2ACP056, 17AI2ACP256,
17RI2ACP056, 17RI2ACP256, 17AI2ACP709

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH661V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FH661V-AS05S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -0716

Yellow Paint (11.5 oz. Aerosol)	759-3940
Yellow Paint (Quart)	759-3945
Yellow Paint (.6 oz. Bottle)	759-04055

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2009

Factory Model Number: 17AI2ACP010, 17AI2ACP056

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR651V-AS04
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	39.3 ft. lbs. @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-99999-0384
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7007
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-0711
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7017
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FR651V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2009-2010

Factory Model Number: 17AI2ACP010, 17AI2ACP056, 17AI2ACP256
17WI2ACP010, 17WI2ACP056

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR651V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	39.3 ft. lbs. @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-99999-0384
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7007
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-0711
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7017
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FR651V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 VT

YEAR: 2009

Factory Model Number: 17VK2ACP010, 17VK2ACP009

24 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Intek (Vertical)
Model/Type/Spec	44M777-0729-B1
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	24 HP
Peak Torque	Not Available
Displacement	44.2 cu in. (725cc)
Bore	3.12"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-792105
Pre Filter	BS-792303
Oil Filter	BS-795890
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-797890

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	BS-794360
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	BS-44Q777-0037
Short Block	BS-698172
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54

YEAR: 2009

Factory Model Number: 17AI2ACK010, 17AI2ACK710, 17AI2ACK709,
17AI2ACK056

23 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS04
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP (17.2 kW)
Peak Torque	39.5 ft. lbs @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54 KW

YEAR: 2009-2012

Factory Model Number: 17AI2ACK010, 17AI2ACK056, 17AI2ACK256
17WI2ACK010, 17WI2ACK056

23 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP (17.2 kW)
Peak Torque	39.5 ft. lbs @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54

YEAR: 2007-2009

Factory Model Number: 17AI2ACK010, 17AI2ACK710, 17AI2ACK709,
17AI2ACK056

25 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FH (Vertical)
Model/Type/Spec	FH721V-AW04
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	25 HP
Peak Torque	Not Available
Displacement	41.19 cu in. (675 mL)
Bore	2.96"
Stroke	2.99"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FH721V-ES25S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	20 H.P. Courage	Single	Hydro	2010
RZT 50	22 H.P. Kawasaki	Twin	Hydro	2010
RZT 50 VT	26 H.P. Intek	Twin	Hydro	2010
RZT 54	23 H.P. Kawasaki	Twin	Hydro	2010

MODEL: RZT 42

YEAR: 2009-2010

Factory Model Number: 17AE2ACG010

20 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 6.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-5.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV600-0221
No. Of Cylinders	1
Horse Power <small>Rated By Manufacturer</small>	20 HP (14.9 kW)
Peak Torque	Not Available
Displacement	36.4 cu in. (597cc)
Bore	3.70"
Stroke	3.38"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.007" (0.178 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	1.6 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-20-883-06-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-20-584-03-S
Points	Not Applicable
Carb Kit	KH-12-757-03

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-04439
Muffler	751-0617C
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV600-0225
Short Block	KH-20-522-05
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50

YEAR: 2009-2010

Factory Model Number: 17AI2ACP010, 17AI2ACP056, 17AI2ACP256
17WI2ACP010, 17WI2ACP056

22 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR651V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP
Peak Torque	39.3 ft. lbs. @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-99999-0384
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7007
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-0711
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KM-21066-7017
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FR651V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 VT

YEAR: 2010

Factory Model Number: 17VK2ACP010, 17VK2ACP009

26 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Briggs & Stratton
Model Series	Intek (Vertical)
Model/Type/Spec	44P777-0784
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	26 HP
Peak Torque	Not Available
Displacement	44.2 cu in. (725cc)
Bore	3.12"
Stroke	2.89"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.012"

CAPACITIES:

Engine Crankcase	2.0 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	BS-792105
Pre Filter	BS-792303
Oil Filter	BS-696584
Fuel Filter	BS-691035
Spark Plug	759-3336
Armature	BS-691060
Points	Not Applicable
Carb Kit	BS-792455

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	BS-794360
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	BS-44P777-0027
Short Block	BS-698172
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54 KW

YEAR: 2009-2012

Factory Model Number: 17AI2ACK010, 17AI2ACK056, 17AI2ACK256
17WI2ACK010, 17WI2ACK056

23 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP (17.2 kW)
Peak Torque	39.5 ft. lbs @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	22 H.P. Courage	Twin	Hydro	2011
RZT 50 KW	23 H.P. Kawasaki	Twin	Hydro	2011
RZT 50 KH	25 H.P. Courage	Twin	Hydro	2011
RZT 54 KW	23 H.P. Kawasaki	Twin	Hydro	2011
RZT 54 KH	26 H.P. Courage	Twin	Hydro	2011

MODEL: RZT 42

YEAR: 2011-2012

Factory Model Number: 17AF2ACS010, 17WF2ACS010, 17YF2ACS010
17WF2ACS009, 17WF2ACS056

22 H.P. Hydro Drive
Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 8.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV715-3027
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP (16.4 kW)
Peak Torque	Not Available
Displacement	44.0 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV715-3027
Short Block	KH-32-522-07
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 KW

YEAR: 2011-2012

Factory Model Number: 17AI2ACK010, 17AI2ACP056, 17WI2ACP010, 17WI2ACP056
17WF2ACK010, 17WI2ACK056, 17YI2ACP010, 17YI2ACP056

23 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP
Peak Torque	39.5 ft. lbs. @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 KH

YEAR: 2011

Factory Model Number: 17AF2ACP010,
17WF2ACP010, 17WF2ACP009

25 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV730-3043
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	25 HP (18.6 kW)
Peak Torque	Not Available
Displacement	44.00 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KH-SV730-3043
Short Block	KH-32-522-07
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54 KW

YEAR: 2009-2012

Factory Model Number: 17AI2ACK010, 17AI2ACK056, 17AI2ACK256
17WI2ACK010, 17WI2ACK056

23 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP (17.2 kW)
Peak Torque	39.5 ft. lbs @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 54 KH

YEAR: 2011

Factory Model Number: 17YF2ACP010, 17YF2ACP009

26 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-7.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV735-3027
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	26 HP (19.4 kW)
Peak Torque	Not Available
Displacement	44.00 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KH-SV725-3030
Short Block	KH-32-522-07
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

RZT 42	22 H.P. Courage	Twin	Hydro	2012
RZT 50 KH	23 H.P. Courage	Twin	Hydro	2012
RZT 50 KH	24 H.P. Courage	Twin	Hydro	2012
RZT 50 KW	23 H.P. Kawasaki	Twin	Hydro	2012
RZT 54 KW	23 H.P. Kawasaki	Twin	Hydro	2012

MODEL: RZT 42

YEAR: 2011-2012

Factory Model Number: 17AF2ACS010, 17WF2ACS010, 17YF2ACS010
 17WF2ACS009, 17WF2ACS056

22 H.P. Hydro Drive
 Electric P.T.O. / 42" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	45.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	480 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	11" x 4"-5"
Rear Wheel Tire Size	18" x 8.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV715-3027
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	22 HP (16.4 kW)
Peak Torque	Not Available
Displacement	44.0 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1600 R.P.M.
Max. Speed (No Load)	3350 R.P.M.
Max. Speed (Full Load)	3300 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-12-050-01-S
Fuel Filter	KH-20-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-04439
Muffler	751-0616B
Battery	925-1707D
P.T.O. Clutch	917-04376A

ENGINE:

Complete Engine	KH-SV715-3027
Short Block	KH-32-522-07
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 KH

YEAR: 2012

Factory Model Number: 17YF2ACP010, 17YF2ACP009

23 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV720-3050
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP (17.2 kW)
Peak Torque	Not Available
Displacement	44.00 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KH-SV720-3050
Short Block	KH-32-522-07
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 KH

YEAR: 2012

Factory Model Number: 17YF2ACP010, 17YF2ACP009

24 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	54.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kohler
Model Series	Courage (Vertical)
Model/Type/Spec	SV725-3030
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	24 HP (17.9 kW)
Peak Torque	Not Available
Displacement	44.00 cu in. (725cc)
Bore	3.27"
Stroke	2.64"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.005" (0.127 mm)
Valve Lash (Exhaust)	0.005" (0.127 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.011"-0.013"

CAPACITIES:

Engine Crankcase	1.8 qts. (A)
Coolant	Not Applicable
Transmission	112 oz. Both Transaxles (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 10W30	737-3030A
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KH-32-883-03-S1
Pre Filter	See Air Filter
Oil Filter	KH-52-050-02-S
Fuel Filter	KH-25-050-22-S1
Spark Plug	759-3336
Armature	KH-24-584-45-S
Points	Not Applicable
Carb Kit	KH-24-757-46-S

TRACTOR MAINTENANCE PARTS:

Transmission Filter	Not Applicable
Voltage Regulator	KH-41-403-10-S
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KH-SV725-3030
Short Block	KH-32-522-07
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04021-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.

MODEL: RZT 50 KW

YEAR: 2011-2012

Factory Model Number: 17AI2ACK010, 17AI2ACP056, 17WI2ACP010, 17WI2ACP056
17WF2ACK010, 17WI2ACK056, 17YI2ACP010, 17YI2ACP056

23 H.P. Hydro Drive
Electric P.T.O. / 50" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	527 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	18" x 9.5"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.0 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP
Peak Torque	39.5 ft. lbs. @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-04552

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

MODEL: RZT 54 KW

YEAR: 2009-2012

Factory Model Number: 17AI2ACK010, 17AI2ACK056, 17AI2ACK256
17WI2ACK010, 17WI2ACK056

23 H.P. Hydro Drive
Electric P.T.O. / 54" Deck

GENERAL INFO:

Length (Over-All)	67.0"
Width (Over-All)	57.0"
Height (Over-All)	Not Available
Ground Clearance	Not Available
Weight (Approximate)	557 lbs.
Engine Type	Gas (Air Cooled)
Electrical System	12v Negative Ground

GENERAL INFO:

Wheelbase	43.50"
Tread Front/Rear	Rib/Turf
Turning Radius	0"
Front Wheel Tire Size	13" x 5.0"-6"
Rear Wheel Tire Size	20" x 10"-8
Trans/Differential Type	Aluminum, Intergrated
Forward Speed	0-6.5 mph
Reverse Speed	0-3.0 mph

ENGINE SPECS:

Make	Kawasaki
Model Series	FR (Vertical)
Model/Type/Spec	FR691V-AS05
No. Of Cylinders	2
Horse Power <small>Rated By Manufacturer</small>	23 HP (17.2 kW)
Peak Torque	39.5 ft. lbs @ 2,200 R.P.M.
Displacement	44.3 cu in. (726cc)
Bore	3.10"
Stroke	3.00"

ENGINE SPECS:

Idle Speed	1550 R.P.M.
Max. Speed (No Load)	3600 R.P.M.
Max. Speed (Full Load)	3450 R.P.M.
Valve Lash (Intake)	0.003" (0.0762 mm)
Valve Lash (Exhaust)	0.003" (0.0762 mm)
Ignition Type	Electronic
Spark Plug Gap	0.030"
Mag Air Gap	0.008"-0.016"

CAPACITIES:

Engine Crankcase	1.9 qts. (A)
Coolant	Not Applicable
Transmission	70.3 oz. per Transaxle (B)
Transaxle	Not Applicable
Creeper Drive Housing	Not Applicable
Front Axle	Not Applicable
Fuel Tank	3.0 gal.

FLUIDS:

(A) SAE 30	737-3029
(B) Drive System + Fluid	737-3120
(C) 135H EP Gear Lube 85W-140	737-3065
(D) 251 EP Chassis Lubricant	737-3034

ENGINE MAINTENANCE PARTS:

Air Filter	KM-11013-7027
Pre Filter	KM-11013-7009
Oil Filter	KM-49065-7010
Fuel Filter	KM-49019-0014
Spark Plug	KM-BPR4ES
Armature	KM-21171-7034
Points	Not Applicable
Carb Kit	Not Available

TRACTOR MAINTENANCE PARTS:

Transmission Filter	HG-52114P
Voltage Regulator	KM-21066-7011
Solenoid	725-1426A
Muffler	751-0616A
Battery	925-1707D
P.T.O. Clutch	917-05001
P.T.O. Clutch Harness 11.625"	725-06019

ENGINE:

Complete Engine	KM-FR691V-AS00S
Short Block	Not Available
Mini Block	Not Available

WARRANTY:

Limited Residential	3 Year / 120 Hrs.
Engine	3 Year / 120 Hrs.
P.T.O. Clutch	3 Year / 120 Hrs.

BEIGE POWDERED PAINT CODE -0499

Beige Paint (11.5 oz. Aerosol)	759-3735
Beige Paint (Quart)	759-3736
Beige Paint (.6 oz. Bottle)	759-3674

YELLOW POWDERED PAINT CODE -4021

Yellow Paint (11.5 oz. Aerosol)	788S04021
Yellow Paint (Quart)	788L04201-QT
Yellow Paint (.6 oz. Bottle)	788T04021

Part Numbers and Specifications Subject To Change Without Notice.